

# THINNER 762

Product No. 6762

<b>TYPE</b>	Low Molecular Weight Ketone
<b>USES</b>	For thinning Sipoxyshield 612 and for cleaning of tools and equipment after the use of Epoxies.
<b>APPEARANCE</b>	Clear Liquid
<b>DENSITY</b>	0.79 kg/Liter
<b>FLASH POINT</b>	4°C
<b>BOILING RANGE</b>	55°C – 58°C
<b>PACK SIZE</b>	5 and 20 Liter
<b>STORAGE</b>	In original sealed containers indoors at temperatures between 5 and 40°C and a relative humidity below 70%.
<b>SHELF LIFE</b>	2 years if stored in accordance with the instructions above.
<b>SAFETY PRECAUTIONS</b>	<p>During application take normal precautions such as wearing safety gloves, facemasks and eye shields. Avoid breathing vapour, ensure adequate ventilation during use. Observe all statutory local bye-laws with respect to health and safety together with the laws governing storage of flammable liquid products.</p> <p>Keep material away from sparks and open flames. Keep out of reach of children.</p> <p>In case of skin contact washes thoroughly with soap and water.</p> <p>In case of eye contact flush immediately with water. If swallowed, call physician immediately. Do not induce vomiting.</p>